



**PREMIER**  
**LUBRICANTS FACTORY LLC**



## KEY-DATA

**ATC GERMANY**

**0W-8**  
**engine oil**

### MANUFACTURER APPROVALS

ATC Germany 0W-8 Engine Oil is formulated to meet modern engine lubrication requirements and is designed for vehicles requiring ultra-low viscosity lubricants.

Performance Standards:

API performance level (depending on application)  
ILSAC specifications (depending on application)  
Designed for modern hybrid and fuel-efficient engines

### Properties and Benefits

- Ultra-low viscosity technology for improved fuel economy
- Excellent cold-start protection
- Fast oil circulation during engine startup
- Reduces friction between moving engine parts
- Provides strong anti-wear protection
- Excellent thermal and oxidation stability
- Helps maintain engine cleanliness
- Protects against sludge and deposits
- Supports smooth and efficient engine performance

### PRODUCT DESCRIPTION

ATC Germany 0W-8 Premium Engine Oil is an advanced fully synthetic lubricant specially developed for modern high-efficiency engines requiring ultra-low viscosity oil. Its advanced formulation provides excellent cold-start performance, reduced internal friction, and reliable engine protection.

The low viscosity technology helps improve fuel efficiency while maintaining strong wear protection, engine cleanliness, and stable lubrication under demanding operating conditions.

### APPLICATIONS

- ATC Germany 0W-8 Premium Engine Oil is recommended for:
  - Modern gasoline engines
  - Hybrid vehicles
  - Fuel-efficient passenger cars
  - Vehicles requiring SAE 0W-8 viscosity grade
- Suitable for advanced engine designs where low-viscosity lubrication is required.

PREMIER  
LUBRICANTS  
FACTORY LLC



## CUSTOMER BENEFITS

- Helps improve fuel efficiency
- Provides faster protection during cold starts
- Helps reduce engine wear
- Supports longer engine life
- Maintains clean engine components
- Provides smooth and quiet engine operation
- Designed for modern high-performance engines

## CHARACTERISTICS

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	0W-8
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	24.8
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	5.1
Density at 15°C	kg/m <sup>3</sup>	ASTM D1298	844
Viscosity index	-	ASTM D2270	140
Pour point	°C	ASTM D97	-39
OC Flash point	°C	ASTM D92	235

## RECOMMENDATIONS FOR USE

- Always check the vehicle manufacturer's owner manual before use.
- 
- Use only in engines requiring SAE 0W-8 lubricant specifications.
- 
- Do not mix with other oils unless approved by the manufacturer.
- 
- Follow recommended oil change intervals for maximum engine performance.

## HEALTH, SAFETY AND THE ENVIRONMENT

- Avoid prolonged or repeated skin contact
- 
- Use protective gloves when handling
- 
- In case of eye contact, rinse immediately with clean water
- 
- Do not ingest
- 
- Dispose of used oil in accordance with local environmental regulations
- 
- Do not discharge into drains, soil, or water systems

• This product should not be used for any purposes other than the ones for which it is intended.

PREMIER  
LUBRICANTS  
FACTORY, LLC