



PREMIER
LUBRICANTS FACTORY LLC



KEY-DATA

ATC GERMANY

10W-30
ENGINE OIL

MANUFACTURER APPROVALS

ATC Germany 10W-30 is formulated to meet the requirements of:

SAE Viscosity Grade: 10W-30
API Performance Level: Suitable for gasoline and diesel engines (e.g., API SP / SN depending on formulation)
ACEA Standards: Applicable performance levels depending on formulation

Always verify compatibility with the vehicle manufacturer's specification before use.

PRODUCT DESCRIPTION

ATC Germany 10W-30 is a high-performance engine oil formulated to provide reliable protection, engine cleanliness, and efficient performance for gasoline and diesel engines. Its advanced formulation helps reduce wear, control deposits, and maintain engine efficiency under a wide range of operating conditions.

The balanced viscosity characteristics ensure excellent lubrication during start-up and dependable protection at normal operating temperatures.

APPLICATIONS

- ATC Germany 10W-30 is suitable for use in:
 - Gasoline engines
 - Light-duty diesel engines
 - Passenger cars
 - Light commercial vehicles
 - Naturally aspirated and turbocharged engines
 - Vehicles requiring SAE 10W-30 engine oil

Properties and Benefits

- ATC Germany Engine Protection: Helps maximize engine life and reliability.
- ATC Germany Efficient Performance: Supports smooth and efficient engine operation.
- ATC Germany Reduced Maintenance: Helps minimize engine deposits and wear-related issues.
- ATC Germany Long Service Life: Maintains performance throughout the oil drain interval.
- ATC Germany Reliable Operation: Provides dependable protection in various driving conditions.

PREMIER
LUBRICANTS
FACTORY LLC



CUSTOMER BENEFITS

- **ATC Germany Reliability:** Consistent engine performance and protection.
- **ATC Germany Cost Efficiency:** Helps reduce maintenance and operating costs.
- **ATC Germany Durability:** Long-lasting protection against wear and deposits.
- **ATC Germany Performance:** Suitable for everyday and demanding driving conditions.

CHARACTERISTICS

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	10W-30
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	71.48
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	10.91
Density at 15°C	kg/m ³	ASTM D1298	882
Viscosity index	-	ASTM D2270	142
Pour point	°C	ASTM D97	-33
OC Flash point	°C	ASTM D92	200

RECOMMENDATIONS FOR USE

- ATC Germany 10W-30 should be used where SAE 10W-30 viscosity grade is specified by the vehicle manufacturer.
- Always follow the manufacturer's recommendations regarding oil specifications and service intervals.
- Check oil levels regularly and maintain within recommended limits.
- Replace oil and filter according to the recommended maintenance schedule.
- Do not mix with oils of different specifications unless approved.

HEALTH, SAFETY AND THE ENVIRONMENT

- Avoid prolonged or repeated skin contact
- Use protective gloves when handling
- In case of eye contact, rinse immediately with clean water
- Do not ingest
- Dispose of used oil in accordance with local environmental regulations
- Do not discharge into drains, soil, or water systems

• This product should not be used for any purposes other than the ones for which it is intended.