



PREMIER
LUBRICANTS FACTORY LLC



KEY-DATA

ATC GERMANY

15W-40
ENGINE OIL

MANUFACTURER APPROVALS

ATC Germany 15W-40 is formulated to meet the requirements of:

SAE Viscosity Grade: 15W-40
API Performance Level: Suitable for gasoline and diesel engines (e.g., API CI-4 / CH-4 / SL depending on formulation)

Always verify compatibility with the manufacturer's specification before use.

Properties and Benefits

- ATC Germany Viscosity Performance: Maintains stable viscosity under varying temperature conditions.
- ATC Germany Thermal Stability: High resistance to oxidation and thermal degradation.
- ATC Germany Wear Protection: Provides strong protection against engine wear.
- ATC Germany Detergency: Helps control sludge, soot, and deposit formation.
- ATC Germany Load Carrying Capacity: Suitable for heavy-duty operating conditions.
- ATC Germany Compatibility: Compatible with engine seals and materials.

PRODUCT DESCRIPTION

ATC Germany 15W-40 is a high-performance multi-grade engine oil formulated to provide reliable protection, durability, and cleanliness for engines operating under a wide range of conditions. It is designed for gasoline and diesel engines requiring an SAE 15W-40 viscosity grade.

The formulation delivers strong lubrication, good thermal stability, and effective protection against wear, deposits, and oxidation, making it suitable for both on-road and off-road applications.

APPLICATIONS

- ATC Germany 15W-40 is suitable for use in:
 - Passenger cars with gasoline engines
 - Light and heavy-duty diesel engines
 - Commercial vehicles and fleet operations
 - Naturally aspirated and turbocharged engines
 - Agricultural and construction equipment (where applicable)

PREMIER
LUBRICANTS
FACTORY LLC



CUSTOMER BENEFITS

- ATC Germany Durability: Long-lasting engine protection
- ATC Germany Cost Efficiency: Helps reduce maintenance and downtime
- ATC Germany Reliability: Stable performance in daily and heavy-duty use
- ATC Germany Protection: Minimizes risk of engine damage

CHARACTERISTICS

TEST	UNIT	TEST METHOD	RESULT
Density at 15 °C	kg/m ³	ASTM D1298	888
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	98.7
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	13.4
Viscosity index	-	ASTM D2270	136
Pour point	°C	ASTM D97	-30
Flash Point	°C	ASTM D92	236
T.B.N	mg KOH/g	ASTM D2896	11
Sulphated Ash	% m/m	ASTM D874	1.45

RECOMMENDATIONS FOR USE

- ATC Germany 15W-40 should be used where SAE 15W-40 viscosity grade is specified by the equipment or vehicle manufacturer.
- Always follow the manufacturer's recommendations for oil specification and service intervals.
- Do not mix with oils of different specifications unless approved.
- Check oil level regularly and maintain within recommended limits.
- Replace oil and filter according to maintenance schedules.

HEALTH, SAFETY AND THE ENVIRONMENT

- Avoid prolonged or repeated skin contact
- Use protective gloves when handling
- In case of eye contact, rinse immediately with clean water
- Do not ingest
- Dispose of used oil in accordance with local environmental regulations
- Do not discharge into drains, soil, or water systems

• This product should not be used for any purposes other than the ones for which it is intended.