



PREMIER
LUBRICANTS FACTORY LLC



KEY-DATA

ATC GERMANY

5W-40
ENGINE OIL

MANUFACTURER APPROVALS

ATC Germany 5W-40 is formulated to meet the requirements of:

SAE Viscosity Grade: 5W-40
API Performance Level: Suitable for gasoline and diesel engines (e.g., API SN / CF depending on formulation)
ACEA Standards: A3/B4 (depending on formulation)

Always verify compatibility with the vehicle manufacturer's specification before use.

Properties and Benefits

- ATC Germany Engine Protection: Extends engine life by reducing wear.
- ATC Germany Performance: Supports smooth and efficient engine operation.
- ATC Germany Engine Cleanliness: Keeps engine components clean and free from deposits.
- ATC Germany Reliability: Provides consistent performance under demanding conditions.
- ATC Germany Versatility: Suitable for a wide range of vehicles and driving environments

PRODUCT DESCRIPTION

ATC Germany 5W-40 is a high-performance, fully synthetic engine oil developed to provide excellent protection, cleanliness, and performance for modern gasoline and diesel engines. It is designed to operate effectively under a wide range of temperatures and driving conditions.

The advanced formulation delivers strong wear protection, high thermal stability, and resistance to oxidation, ensuring long engine life and reliable operation.

APPLICATIONS

- ATC Germany 5W-40 is suitable for use in:
 - Passenger cars with gasoline engines
 - Light-duty diesel engines
 - Turbocharged and naturally aspirated engines
 - High-performance and modern engines
 - Vehicles operating under normal to severe driving conditions

PREMIER
LUBRICANTS
FACTORY LLC



CUSTOMER BENEFITS

- ATC Germany Reliability: Stable and dependable engine performance
- ATC Germany Protection: Reduces risk of engine damage and wear
- ATC Germany Cost Efficiency: Helps lower maintenance costs
- ATC Germany Comfort: Smooth and responsive driving experience

CHARACTERISTICS

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	5W-40
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	83.9
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	13.9
Density at 15°C	kg/m ³	ASTM D4052	850
Viscosity index	-	ASTM D2270	170
Pour point	°C	ASTM D97	-27
OC Flash point	°C	ASTM D92	240

RECOMMENDATIONS FOR USE

- ATC Germany 5W-40 should be used where SAE 5W-40 viscosity grade is specified by the manufacturer.
- Always follow the manufacturer's recommendations for oil specifications and service intervals.
- Do not mix with oils of different specifications unless approved.
- Check oil level regularly and maintain within recommended limits.
- Replace oil and filter according to maintenance schedules.

HEALTH, SAFETY AND THE ENVIRONMENT

- Avoid prolonged or repeated skin contact
- Use protective gloves when handling
- In case of eye contact, rinse immediately with clean water
- Do not ingest
- Dispose of used oil in accordance with local environmental regulations
- Do not discharge into drains, soil, or water systems

• This product should not be used for any purposes other than the ones for which it is intended.