



PREMIER
LUBRICANTS FACTORY LLC



KEY-DATA

ATC GERMANY

DEXRON II
ATF

MANUFACTURER APPROVALS

ATC Germany ATF DEXRON® II is formulated to meet or exceed the performance requirements of:

General Motors DEXRON® II D
Allison C-4
Caterpillar TO-2
Ford M2C138-CJ
Ford M2C166-H
MAN 339 Type Z1
MAN 339 Type V1
Mercedes-Benz MB 236.1
Voith H55.6335
ZF TE-ML 03D
ZF TE-ML 04D

Properties and Benefits

- Smooth and reliable gear shifting
- Excellent oxidation and thermal stability
- Superior wear protection for transmission components
- Outstanding friction characteristics
- Protection against rust and corrosion
- Good low-temperature fluidity
- Excellent seal compatibility
- Reduced sludge and deposit formation
- Long service life

PRODUCT DESCRIPTION

ATC Germany ATF DEXRON® II is a high-quality automatic transmission fluid formulated with premium base oils and advanced additive technology. It is designed to provide smooth gear shifting, excellent wear protection, oxidation resistance, and reliable performance in automatic transmissions, power steering systems, and hydraulic applications requiring a DEXRON® II type fluid.

APPLICATIONS

- Recommended for:
- Automatic transmissions requiring DEXRON® II fluids
- Power steering systems
- Hydraulic systems
- Torque converters
- Commercial vehicles
- Passenger cars
- Construction and agricultural equipment where ATF DEXRON® II is specified

**PREMIER
LUBRICANTS
FACTORY LLC**



CUSTOMER BENEFITS

- Enhances transmission performance
- Extends transmission life
- Reduces maintenance costs
- Improves shifting comfort
- Protects critical transmission components
- Provides reliable operation under varying temperatures
- Helps maintain system cleanliness

CHARACTERISTICS

Viscosity Class		SKOROIL ATF II DEXRON
Density 15 °C g/ml	ASTM D-4052	Max.0.870
Flash Point COC, °C	ASTM D-92	Min.200
Kinematic Viscosity mm ² /s at 100°C	ASTM D-445	6.4-8.9
Viscosity Index	ASTM D-2270	Min.150
Pour Point, °C	ASTM D-97	Max.-35

RECOMMENDATIONS FOR USE

- Use where DEXRON® II performance level is specified by the equipment manufacturer. Follow manufacturer recommendations regarding drain intervals and maintenance procedures.
- Do not use where DEXRON® VI or other specialized fluids are specifically required unless approved by the manufacturer.

HEALTH, SAFETY AND THE ENVIRONMENT

- Avoid prolonged or repeated skin contact. Wash thoroughly after handling. Store in a cool, dry place away from direct sunlight and sources of ignition. Keep containers tightly closed when not in use.
- Refer to the Safety Data Sheet (SDS) for complete health, safety, and environmental information.
- ATC Germany – Advanced Transmission Protection for Smooth and Reliable Performance

• This product should not be used for any purposes other than the ones for which it is intended.